



Partition wall wood fiber Therm

Building system for partition walls in BetonWood cement bonded particle boards and wood fiber Therm fixed on wood or x-lam structure

The complete building system for internal and partition walls with high performances and fire resistant. Partition wall wood fiber Therm is easy and fast to install, it guarantees the maximum comfort and the maximum durability over time.
Complete system: panels, skimming products, fixing products and accessories

STRATIGRAPHY	DESCRIPTION	QUANTITY	PRICE	TOTAL
1 Wood frame	Wood frame structure			
5 Wood fiber panels FiberTherm 160	<p>Supply and installation of the thermo-acoustic insulation of the vertical wall with FiberTherm wood fiber panels with joined joints. The panels are made of wood fiber with density $\delta = 160 \text{ Kg / m}^3$, are produced with a wet system, in compliance with EN 13171 and EN 13986 standards under constant quality control.</p> <p>The material is characterized by the following thermodynamic characteristics: coefficient of thermal conductivity $\lambda = 0.039 \text{ W / mK}$, specific heat $c = 2100 \text{ J / Kg K}$, coefficient of resistance to vapor penetration $\mu = 5$ and reaction to fire class E, according to EN 13501-1 standard.</p> <p>The dimensions of the panels correspond to ... mm for a thickness of ... mm.</p> <p>The wood used in the processing of the panels comes from forests controlled by FSC reforestation cycles.</p>			
2 Cement bonded particle boards BetonWood N	<p>The BetonWood N cement bonded particle boards, with high density (1350 Kg/m^3), made of Portland-type cement conglomerate and debarked Pine wood fiber. These panels have the following thermo-dynamics characteristics: thermal conductivity coefficient $\lambda=0,26 \text{ W/mK}$, specific heat $c=1,88 \text{ KJ/Kg K}$, coefficient of resistance to vapor penetration $\mu=22,6$ and reaction to fire class A2-fl-s1, according to the standard EN 13501-1.</p> <p>Available in the following sizes: 870x515 mm, 1012x515 mm, 1025x515 mm, 1200x500 mm, 1220x500 mm. Thicknesses from 18 to 22 mm.</p> <p>Available with stepped, tongue&groove and sharp edges.</p>			
3 Screws NF57	The screw has a special anti-corrosion coating that guarantees a 1,000-hour salt spray resistance. Under-head with very sharp self-sinking fins for a perfect housing of the head flush with the slab. Spoon tip (spoon) with very high perforation capacity.			
4 Plasterboards	Plasterboards			



The functionality of the system will be covered by a BetonWood guarantee for the characteristics of air tightness, water proofing and isolation of the technological package. The warranty will be documented with the appropriate Certificate and Certificate of Assurance that will be delivered at the end of the work to the DD.LL. from the same layer. The forms are available on the BetonWood website as well as the technical indications, the application matrix and the exclusion clauses.

TOTAL AMOUNT